VELOGY PLUS/PLEXEO TANK MIX LIST

The following tank mixes have been tested for physical compatibility with VELOGY PLUS/PLEXEO at recommended rates of use and will mix in the sprayer tank. No tests have been undertaken on crop safety or product performance therefore, use is at the user's own risk. Syngenta UK Ltd will support the physical compatibility of 2 or 3-way tank mixes of VELOGY PLUS/PLEXEO with any of the fungicides, herbicides, insecticides or PGRs listed. For further information on compatibilities, contact Syngenta UK Ltd on 0800 169 6058.

FUNGICIDES

Arizona Talius Vareon

Vegas

HERBICIDES

Answer SX Avro SX AXIAL PRO BiPlay SX Broadway Star Duplosan KV Pixxaro Presite SX Starane Hi-Load Topik + oil

PGRs

BASF 3C Chlormequat 750 Canopy Cerone MODDUS MODDUS + chlormequat Selon SONIS SONIS + chormequat Terpal

TRACE ELEMENTS

Syngenta UK Ltd will support the tank mixing of any of the named trace elements with an existing 2 or 3-way tank mix including VELOGY PLUS/PLEXEO. Syngenta UK Ltd advise that the trace element part of the tank mix is added to the sprayer tank last with constant agitation and the mixture is sprayed without delay.

Bittersalz

Intracrop Magistrate

Intracrop Uplift

NOTES

Before using any tank mixture, consult and comply with the recommendations of the partner products. Each product should be added separately to the bulk of the water in the spray tank and thoroughly mixed before adding the next chemical. Always use constant agitation of the sprayer tank during mixing, transportation and application. Spray immediately.

Buffer zone: 6 metres Rainfastness: After 1 hour

> Use plant protection products safely. Always read the label and product information before use. ©Syngenta AG, October 2020



For further information contact us on 0800 169 6058 e-mail: <u>customer.services@syngenta.com</u>

Syngenta UK Ltd, Fulbourn, Cambridge CB21 5XE. Tel: (01223) 883400. Fax: (01223) 281245. Website: http://www.syngenta.co.uk